

## **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application:

### **Listing of Claims**

1. (original) A proxy for use with a user device operating in a heterogeneous wireless network environment, said proxy comprising:
  - means for determining that said user device is in an area of overlap by different networks within said environment; and
  - means for handing off said user device from a first network to a second network.
2. (original) A proxy according to claim 1, wherein said determining means combines both event-driven and polling-based schemes for detecting changes in network conditions.
3. (original) A proxy according to claim 1, wherein said second network operates at a higher bandwidth than said first network.
4. (original) A proxy according to claim 1, further comprising means to track an ongoing session with said user device.
5. (original) A proxy according to claim 4, wherein said tracking means is a byte counter.
6. (original) A proxy according to claim 4, wherein said session is a HTTP session.

7. (original) A proxy according to claim 4, wherein said session is a SNMP session, a POP3 session, an IMAP session, or a streaming session.

8. (currently amended) A method of handing off a user device from a first network to a second network, said method comprising:

establishing a session on said user device with said first network;

determining by said user device that said user device is in an area where said first network and said second network overlap; and

handing off said user device from said first network to said second network.

9. (original) A method according to claim 8, wherein said determining step comprises:

using an event-driven scheme to detect network events;

using a polling-based scheme to collect general network conditions; and

combining results from said event-driven scheme and said polling-based scheme.

10. (original) A method according to claim 8, wherein said second network operates at a higher bandwidth than said first network.

11. (original) A method according to claim 8, further including the step of tracking the byte count of said session.

12. (original) A method according to claim 8, wherein said session is a HTTP session.

13. (original) A proxy according to claim 8, wherein said session is a SNMP session, a POP3 session, an IMAP session, or a streaming session.

14. (currently amended) An architecture for use in a heterogeneous wireless network environment, said architecture comprising:

a user device having an installed web browser;

a web server;

a proxy interposed between said web browser and ~~said web server~~ heterogeneous wireless network environment; and

an information gateway interposed between the heterogeneous wireless network environment ~~said proxy~~ and said web server.

15. (original) An architecture according to claim 14, wherein said proxy includes  
means for determining that said user device is in an area of overlap by different networks within said environment; and  
means for handing off said user device from a first network to a second network.

16. (original) An architecture according to claim 15, wherein said determining means combines both event-driven and polling-based schemes for detecting changes in network conditions.

17. (original) An architecture according to claim 15, wherein said second network operates at a higher bandwidth than said first network.

18. (original) An architecture according to claim 15, wherein said proxy includes means to track an ongoing session with said user device.

19. (original) An architecture according to claim 18, wherein said tracking means is a byte counter.

20. (currently amended) An architecture according to claim 18, wherein said proxy and said information gateway communicate information from said tracking means so that upon handoff from said first network to said second network, file loading can begin ~~at the point that~~ where file loading was stopped because of said handoff.